# DC BATTERY BACKUP CAPABLE WALL MOUNT GARAGE DOOR OPENER

Wall Mount Design: The simple beauty of an open space.

NEY FEATURES **SPACE-SAVING** Design Maximizes Versatility LIFTING POWER Powers 650 lbs. Doors

**INCLUDED ACCESSORIES:** 

**3-BUTTON REMOTE CONTROL** Operates up to 3 openers or MyQ Light Accessories



#### **MYQ® CONTROL PANEL**

Allows any garage door opener manufactured since 1998 to be controlled by your smartphone, tablet or compter (when paired with the Internet Gateway) - provides the upgrade needed to utilize Security+ 2.0 and MyQ Technology.



### **REMOTE LIGHT**

Light your space the way you want to by placing this anywhere in the garage. Uses (2) 100 watt bulbs (not included).



## **POWERFUL ADD-ONS:**

# **INTERNET GATEWAY**



Connects the opener to the Internet, enabling smartphone control ...







**GARAGE DOOR AND GATE MONITOR** Monitors and closes up to 4 garage doors from any room in the house ...



**BATTERY BACKUP** Powers up even when power is out so you can get in your garage ...



## LiftMaster

## **SMART**

MVQ TECHNOLOGY ENABLES YOU TO SECURELY MONITOR AND CONTROL YOUR GARAGE DOOR OPENER AND HOUSELIGHTS WITH YOUR SMARTPHONE, TABLET OR COMPUTER. REQUIRES PURCHASE OF INTERNET GATEWAY (828LM)\*

ALERTS CAN BE RECEIVED AS EMAIL OR POP-UP (PUSH) NOTIFICATIONS ON YOUR MOBILE DEVICE SO THAT YOU ALWAYS KNOW THE STATUS OF YOUR GARAGE DOOR AND HOUSELIGHTS.

## RELIABLE

ULTRA-QUIET ELIMINATES SOUND AND VIBRATION THROUGH THE CEILING - PERFECT IF YOU HAVE A HOME WITH A ROOM ABOVE OR NEXT TO THE GARAGE.

BATTERY BACKUP POWERS UP EVEN WHEN THE POWER'S OUT. (REQUIRES PURCHASE OF 475LM BATTERY BACKUP).

WALL MOUNT DESIGN FREES THE GARAGE CEILING OF HANGING OPERATORS AND RAILS AND OPENS UP THE SPACE FOR ADDITIONAL STORAGE.

**REMOTE LIGHT** DELIVERS 200 WATTS OF LIGHT WITH ADJUSTABLE LIGHT TIME DELAY.

LIFETIME MOTOR AND 5-YEAR PARTS WARRANTY. 1-YEAR BACKUP BATTERY WARRANTY (SOLD SEPARATELY).DELAY.

## SECURE

TIMER-TO-CLOSE AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

**SECURITY+ 2.0**<sup>®</sup> SENDS A NEW CODE WITH EVERY REMOTE CLICK.

MOTION DETECTOR AUTOMATICALLY TURNS ON THE LIGHT.

THE PROTECTOR SYSTEM® AUTO-REVERSES THE DOOR IF THERE'S AN OBSTRUCTION.

POWER LOCK DEADBOLT (041A6102) ENSURES THE DOOR CANNOT BE FORCED OPEN.

\*Linking your MyQ account to a partner may require an additional accessory purchase or subscription fee.

## PRODUCT GUIDE 8500

DC BATTERY BACKUP CAPABLE WALL MOUNT GARAGE DOOR OPENER

## MASTERFUL ENGINEERING.

### MOTOR

- Heavy-Duty 24V DC - Automatic Thermal Protection

  - Permanent Lubrication
- 120V AC
  - 60 Hz Voltage
  - 2.7A Current Rating
  - -UL<sup>®</sup> Listed
  - 6' Power Cord (3-Prong)

### MECHANICS

- Steel Chassis and Plastic Cover
- Internal Chain and Sprocket Drive Mechanism (63:1 Gear Reduction)
- Auto-Force Adjustment for Changing Weather
- and Environmental Conditions
- Electronic Limits for Easy Setup

## STANDARD SPECS.

SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -40°F to 150°F

#### 3-Button Remote Control (893MAX)

- Remote Control: 310, 315 and 390 MHz Tri-Band\*
- Garage Door Opener: Frequency Agile on 310, 315
- and 390 MHz
- Anti-Burglary Coding

\*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

#### ENCRYPTED CONTROLS

SHIPPING.

CARTON 1: 24" x 10" x 12"

- MyQ Control Panel (888LM)

- Power Door Lock (041A6102)

- Cable Tension Monitor

- Remote Light (380LM)

Close Operation features when installed with a sectional door. © 2018 LiftMaster All Rights Reserved

- Garage Door Opener Head (8500)

- 3-Button Remote Control (893MAX)

SHIPPING WEIGHT

(in lbs.)

**CARTONS (1)** 

MyQ<sup>®</sup> Control Panel<sup>®</sup> (888LM)

- MyQand Security+ 2.0 Radio
- Timer-to-Close
- Motion Detecting: Hands free opener lights on
- Light Control: Turns opener lights on/off
- -Lock Mode: Locks out remote controls

31

CARTON

- The Protector System® Safety Reversing Sensors

- Program remote controls, keypads and MyQ Accessories
- -\*Because the radios reside in the control panel, alternate wired control panels should not be used with this operator.
- DC BATTERY BACKUP CABABLE WALL MOUNT GARAGE DOOR OPENER Battery Backup 20 MAX. DOOR WEIGHT 650 lbs.\* 10 7.6" **SPEED** Per second DIMENSIONS for door Max. Door Size: 14 ft. High by 18 ft. Wide. Max 180 Sq Ft. 6" to move upward Headroom Clearance Required: 3 in. from Per second Center of Torsion Bar for door to move downward MyQ<sup>®</sup> RADIO LIGHTING **REMOTE LIGHT** 902–928 MHz (380LM) (( 50-Channel FHSS (Frequency Hopping Spread Spectrum) Provides 2-way communication = from garage door opener and MyQ accessories\*. - Remote light control Enables monitoring and control fixture can be located of garage door openers and anywhere in garage - Number of bulbs: 2 lighting controls via smartphone, tablet or computer.\*\* - Maximum Wattage: 100 x 2 \*MyQ radio disabled in battery - Adjustable Time, backup mode or when using Solid-State Delay Alternate Power System (580LM) (1.5-4.5 minutes) \*\*Requires Internet Gateway Accessory Model (828LM) **HOMELINK® COMPATIBLE** (VERSION 4.0 OR HIGHER\*\*\*) \*\*\*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

## SAFETY AND SECURITY.

- The Protector System Safety Reversing Sensors
- Battery Backup Capable compatible model 475LM (optional accessory)
- Alert-2-Close/Unattended Close Operation<sup>++</sup>
- Motion Detection Feature on Control Panel
- Hands-Free Work Lights On
- Emergency/Quick Release

- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices

300 Windsor Drive, Oak Brook, IL 60523 LittMaster.com Wi-Fl<sup>®</sup> is a registered trademark of Wi-Fl Alliance UL<sup>®</sup> and the UL logo are trademarks of UL LLC © 2017 All Rights Reserved. LMODCA8500 4/18

<sup>++</sup>Note: to reduce the risk of injury to persons, only use Alert-2-Close/Unattended

**LiftMaster** 

8500

## **D SEGURII** n Safety - Ventilation



